9810 Harvester



Standard Features

Upgraded from the 9800 model with refreshed pumps, motors, and hydraulic tank

New hydraulic circuit and drive improvements for almond, walnut, and hazelnut harvesting

Active cooling system enhances bank-out cart performance

Improved efficiency and thermal management for higher productivity

Proven vacuum system for reduced dust and cleaner harvests

Dirt drops through chains before debris removal for superior crop cleanliness

Designed to meet California clean air and water regulations

Extra-large rear balloon tires for maximum flotation and reduced soil compaction

Vacuum housing and tunnel redesigned for easier service access and faster part replacement

Economical, efficient, and streamlined design

Optimized hydraulics that run cooler

Easy belt changes with gearbox

Onboard stowage for PTO shaft

Convenient access to all service points

Specifications

Availability: Worldwide

Minimum Horsepower: 65 HP (single pump), 85 HP

(bank-out option)

PTO Shaft: 44 Series

Gearbox: High-speed, long-life design

Dirt Chain: Twin-rod, belted bar, mesh, tube, and flat

wire (for almond, walnut, hazelnut)

Windrow Capacity: 48"

Length: 237"

Width: 89"

Height: 82"

Wheelbase: 101"

OPTIONS

- » Bank-out hydraulics
- » Paddle wheels
- » Hydraulic hitch

- » Camer
- » Tractor-controlled work lights
- » 2-speed elevator

