

Shockwave Monoboam



Standard Features

173HP B4.5 Cummins Stage V turbo-diesel engine with a hydraulically-reversing engine-driven fan.

R3 Magnum shaker head with 24" oval pads

- Externally-greasable bearings
- High-tensile steel construction, A514 grade
- Single belt drive and clamp cylinder
- Hydraulic head brake
- Quick-change patterns
- Automatic sling lubrication

Heated and Air-Conditioned Cabin

Hehr glass (windshield and door)

Back-up Camera

LED night lights

Color monitor

Hydrostatic drive with 19:1 ratio (24:1 available)


Sweeper fingers or sweeper brushes

Power coat finish

Fluid Capacities: Fuel: 39.4 gal

Diesel Exhaust Fluid (DEF): 10 gal

Hydraulic Oil: 43 gal



3WMB



Dimensions

Travel Length: 19 feet, 1 inch (head folded)
27 feet (head extended)

Width: (Vehicle): 7 feet

Height: 6 feet 8 inches (head folded)
6 feet (head extended)

Wheelbase: 126 inches

Shaker head vertical reach: 15 feet 9 inches
(standard)
18 feet, 9 inches optional 12 ft boom)

Shaker Head Roll: 60 degrees

OPTIONS

- » R4 Magnum shaker head
24" oval pads, 3" opening
- » Air-cooled pads with Nylatron fill
- » Water pads

- » Dual auto brakes
- » Hill Package (24:1 ratio hubs)
- » Tree Seeker I
- » 12 foot boom

- » Angeled head attachment with slider
- » Tracks
- » Shake patterns