

Shockwave Sprint Series VI



Standard Features

173 Hp b4.5 Cummins stage v turbo-diesel engine with a hydraulically-reversing engine-driven fan

R7 magnum shaker head with 24" oval pads

- Externally-greasable bearings
- High-tensile steel construction, A514 grade
- Dual belt drive
- Hydraulic head brake
- Quick-change patterns
- Automatic sling lubrication

Heated and air-coinditioned cabin

Back-up camera

LED night lights

Color monitor


Hydrostatic drive with 19:1 ratio

Sweeper fingers or brushes

Powder coat finish

Fluid Capacities

- Fuel: 70 gal
- DEF: 10 gal
- Hydraulic Oil: 47 gal



SPRINT



LIFTED SPRINT

Dimensions

Travel Length: 19 feet

Width:

- Vehicle: 8 feet, 3 inches (legal load)
- Shaker head down & retracted: 11 feet, 6 inches
- Shaker head down & extended: 14 feet

Height: 5 feet, 10 inches

Wheelbase: 128 inches

Shaker head vertical reach: 7 feet

Shaer carriage:

Side Roll: 20 degrees

- Side Shift: 30 inches

OPTIONS

- » Shift-on-the-fly all wheel drive
- » Air-cooled pads with Nylatron fill
- » Water pads
- » Dual auto brakes
- » Tree Seeker II
- » Hydraulic Lift (18 inch adjustable)
- » Hill package (24:1 ratio drive)
- » Tracks



2700 Colusa Highway, Yuba City, CA 95993
Phone: (530) 673-2822 • Fax: (530) 673-0296

www.Shakermaker.com